
## Pneumatic manipulator - Mechspace Pro 70/70P

The easy-to-use balanced manipulator



Mechspace Pro 70 is available in two models for loads up to 70 kg: a hanging version and a pillarmounted version, which also can be equipped with a mobile footplate for easy repositioning by forklift truck.

The lifter can be delivered balanced for varying loads or with a balance function for two or more permanent loads. The working stroke is 900 mm.



## Technical data


Maximum load	kg	50-70 *
Maximum torque	Nm	500
Length of stroke	mm	900
Noice level	db (A)	<70
Maximum tare weight	kg	100 (hangning model)
Hoisting speed	m/min	0-40
Rotation	0	0-330 (upper and lower)
Medium		Air, non-lubricated
Air consumption	l <sub>n</sub> /stroke	8 **
Working pressure	bar	4-7
Working temperature	°C	5-40
Colour ***		RAL 2009 (orange), 9010 (white)


\* See table below.

\*\* With maximum load.

\*\*\* Other colours on demand.

Working pressure [bar]	Load capacity [kg]
4	50
5	60
5,5	65
6	70
7	70









Movomech AB Kabelvägen 9 SE-291 62 Kristianstad SWEDEN Phone +4 Fax +4 E-mail inf Web ww

+46 (0)44 28 29 00 +46 (0)44 28 29 28 info@movomech.se www.movomech.se